



# HI-TECH®



## Metal Interlocked Floor Finish

A floor finish breakthrough designed specifically to achieve outstanding performance when used in a high speed maintenance program. This high solids finish is formulated with a blend of pressure emulsified thermoplastics which creates a shine superior to conventional acrylic finishes. Unlike many finishes, this product does not contain any dark resins. Once dry, this finish lets the true color of the floor shine through.

### Uses

- Resilient tile
- Terrazzo
- Concrete
- Cork
- Linoleum
- Rubber

### Maintenance

- Moderate burnishing required
- Low/High speed compatible

### Features

- Can be used through Betco's QUICKCOAT® Applicator for enhanced productivity.
- Appearance – Provides wet look gloss.
- Ease – Self leveling and excellent flow for easy application. Self sealing formula reduces costs.
- Versatile – Responds to buffing and burnishing from 300 to 2000+ rpm's.

### Properties

Buffability:	
300 rpm .....	Very good
1000 rpm .....	Excellent
2000 rpm .....	Superb
Color (dried film).....	Water clear
Color (liquid) .....	Milky white
Coverage.....	2,000 - 3,000 square feet/gallon
Drying time .....	20 - 30 minutes
Fragrance .....	Mild
Freeze/thaw stability .....	3 cycles
Gloss (ASTM D 1455-87).....	One coat 80 - 85
	Two coats 90 - 95
Heel mark resistance .....	Very good
Leveling .....	Excellent
pH.....	8.1 - 8.9
Powdering resistance .....	Excellent
Free styrene content.....	0.0
Shelf life.....	1 year



### Directions For Use

Read the entire label before using this product.

**RESTORATIVE MAINTENANCE:** Completely remove all old wax, finish and soil from floor surface following strip procedure instructions on stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 20 - 30 minutes. 4 - 6 coats of finish are recommended. **Note: This product is a self sealing finish, however, if tile is old, worn or porous, initially applying 1 - 2 coats of a sealer will enhance gloss and long term performance.**

**ROUTINE MAINTENANCE:** Sweep large debris and dust mop (using a water based treatment). Damp mop or automatic scrub using a neutral pH cleaner. Buff or burnish the floor as desired. The use of a cleaner/restorer is recommended to condition the floor and extend the time between top scrub and recoating.

**INTERIM MAINTENANCE:** Sweep large debris and dust mop (using a water-based treatment). Top scrub the floor using a top scrub cleaner and recommended floor pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1 - 2 coats of finish as directed above. **Note: Slip resistance meets or exceeds (ASTM D 2047-93) James Machine 0.5 minimum.**

### Safety

Keep out of reach of children. For institutional and commercial use. **CAUTION:** Contains Acrylic Polymers and Glycol Ethers. May cause eye irritation. Avoid contact with eyes.

**FIRST AID:** If splashed on skin or in eyes, flush with large quantities of water. If swallowed, dilute with two glasses of water. Call a physician. If inhaled, remove to fresh air.

### Available In

- Case/4-1 Gallon (3.78 L): Item #61004-00
- Pail/5 Gallon (18.9 L): Item #61005-00
- Box/2-1.125 Gallon Bags (4.25 L): Item #61059-00 (QUICKCOAT®)
- Drum/55 Gallon (208 L): Item #61055-00

Literature Item #61092-92

