

Centaur

CUSTOM LOGO MATS | 54 OZ. NON-WOVEN BERBER



01. White
1000




02. Off-White
1001




03. Glacier
2344




04. Carbon
9859




05. Coal
2098



06. Black
2000




07. Baby Blue
5149




08. Marine Blue
5182




09. Harbor
5181




10. Icy Blue
5157




11. Dark Blue
5154



12. Multi-Color
5155




13. Purple
3090




14. Aqua
6096




15. Green
6042



16. Dark Leaf
6043




17. Grass Green
6022



18. Raven
2343



19. Taupe
2345




20. Toast
1153




21. Tortoise
2048



22. Fall Leaves
6081



23. Dark Brown
7068




24. Espresso
7185




25. Amber
7006



26. Latte
1064




27. Bisque
1099



28. YellowW
1025




29. Gold
1039




30. Orange
3018




31. Pink
3091




32. Red
3014




33. Henna
3031



34. Burgundy
3034




35. Savannah
7178



36. Java
7097



37. Spice
3353



38. Cherry
3138

Casual or elegant, large or small, high or low traffic, our logo or plain mats are the perfect design solution.

This dense 54 oz. material provides seamless style. Its solution-dyed, UV stabilized ASOTA™ polypropylene fiber and hobnail berber pattern make it resilient and easily cut into any shape without edge ravel.

Langhorn
Flooring Concepts

Your Source for
Commercial Fitness Flooring
(707) 823-4455 • www.langhornfci.com

Centaur



indoor/outdoor

CUSTOM LOGO MATTING | 54 OZ. NON-WOVEN BERBER

SUGGESTED USES

Office Environments, Runners, Conference Rooms, Lobbies, Libraries, Retail/Department Stores, Entryways, etc.

Manufacturing Process:	Non-woven/needlepunched
Surface Aspect:	Hobnail (berber) pattern
Fiber:	100% Solution-dyed UV stabilized ASOTA™ polypropylene
Backing:	Premium composite rubber
Pile Height (± 0.5mm):	0.25"
Total Height (± 7.5%):	0.47"
Pile Weight (± 7.5%):	54 oz/sy
Total Weight (± 7.5%):	78 oz/sy
Sheet/Roll Width (± 2%):	6' 7" or 13' 2"

LIMITED WARRANTY

Full Commercial Warranty 5 years

Summary of Warranty

Products must be professionally installed to validate the warranty.

Langhorn Flooring Concepts Inc. warrants Centaur Custom Matting Goods against wear for a period of 5 years in a commercial application. This warranty applies only to material that is properly installed and maintained, while being used as intended and recommended. If the defect is covered by this warranty and is reported to Langhorn Flooring Concepts Inc. within the warranty period, Langhorn Flooring Concepts Inc. will supply new material of same or similar grade to repair or replace the defective material.

• Wear

Defined as complete removal of wear layer, pattern and color due to wear from normal traffic and maintenance. If the wear occurs within 5 years from date of purchase, Langhorn Flooring Concepts Inc. will provide replacement materials or repair, of only the effected area.

• Manufacturing Defects

Langhorn Flooring Concepts Inc. warrants Centaur materials are free from manufacturing defects and will replace defective floor covering and reasonable installation costs for a period of up to five [5] years from date of purchase. Langhorn Flooring Concepts Inc. will not pay labor costs to repair or replace materials that defects were apparent before or at the time of installation.

• Other Limitations

- This warranty is non-transferable
- Manufacturing defect must be reported within 3 months from date of purchase.
- This Warranty covers only properly installed & maintained floors
- Langhorn Flooring Concepts Inc. excluded and will not pay for any consequential or incidental expenses.
- Langhorn Flooring Concepts Inc. reserves the right of final judgment and may refuse claims in certain instances.

*For a copy of the full warranty please ask for a warranty sheet

PACKING & DIMENSIONS

Sheet/Roll Width (± 2%): 6' 7" or 13' 2"

TECHNICAL SPECIFICATIONS

Dimensional Stability (ASTM D7570-09):	Pass
Electrostatic Propensity (EN 1815):	>2kV
Electrical Resistivity (IBM / ICL):	Pass, for R.H. ≥40%
Sound Insulation (ISO 10140-1:2010):	≥21dB
Thermal Retention (ISO 11092):	0.15 m K/W Pass

COLOR FASTNESS

To Light (ISO 105 B02):	5
To Water (ISO 105 E01):	5
To Shampoo (ISO 105 C06):	4-5
To Rubbing (ISO 105 X12):	4 (Dry), 3-4 (Wet)

FLAMMABILITY RATING

Smoke Density (ASTM E662)	Pass
Surface Flammability (FF 1-70 / ASTM D2859)	Pass

LEED-NC

MR Credit 4 | IEQ Credits 4.1, 4.3, 5

MAINTENANCE

Regular vacuuming (Weekly in low-traffic areas, and daily or twice daily in areas with higher traffic) with a motor-driven brush and beater bar can remove up to 80% of surface dirt, and is the easiest way to prolong the life of your carpet.

Regular vacuuming is key to maintaining your carpet, but eventually the carpet color dulls from dirt and grime stuck in the fibers. The dirt is then carried further into the building to form more soil reservoirs. Additionally, the oil content (15%) of the soil causes particles to stick to carpet fiber and resist vacuuming. To restore the carpet to its best condition, frequent light cleaning gives the best result and is often very cost effective.

*For more information, plus instructions for stain removal, consult Langhorn's Resource Center at www.langhornfci.com
Sample swatches have been cut from an overall design; decoration and shade may vary.



YOUR AUTHORIZED SALES REPRESENTATIVE:

LFC_CENTAURLM_012720

Langhorn
Flooring Concepts

