

Meet our most versatile and customizable scrapeand-clean entry system.

Two-n-One hybrid matting system: the smart and versatile combination of Flex-Vinyl – a heel-and-wheel friendly grid entry system – and your choice of durable all-weather walk-off carpet*, together in a single mat.

The distinctive look of Flex-Vinyl's serrated grid scrapes and captures dirt and debris, while the walk-off carpet* wipes away what's left, including excess moisture. Made using Langhorn Flooring Concepts' industry-leading assembly process, Two-n-One Mat is built to withstand medium to high traffic.

Choose from a wide selection of shapes, sizes and colors (single tone or custom logo designs available), or as a semi-permanent wall-to-wall installation. Two-n-One's nearly limitless versatility is one of many ways Langhorn Flooring Concepts makes customizing mats easier than ever.



*Specifications assume Centaur as selected walk off carpeting.

Actual specifications may vary depending on selected walk off carpet.



Two-N-One

Indoor/Outdoor

GRID ENTRY | HYBRID MAT

SUGGESTED USES Indoor entryways or other high-traf	fic areas with no mat well.	contact your Langhorn Flooring Concepts sales representative.					
SPECIFICATIONS (using Centaur C Overall Thickness Grid Thickness Total Carpet Height* Carpet Pile Height* Carpet Pile Weight* Total Carpet Weight* Backing (Grid) Backing (Centaur Carpet*) Edging Material	0.5 in. 0.375 in. 0.47 in. 0.25 in. 54 oz/sy 78 oz/sy Flexible PVC Premium Composite Rubber PVC	*NOTE: Other Langhorn Flooring Concepts sheet/roll goods ava as walk-off carpet, potentially changing specifications marked wi asterisk. Contact your representative for more information. IMPORTANT NOTICE For more information on how to install Two-N-One in your space, contact your Langhorn Flooring Concepts sales representative. NOTES:					
LIMITED WARRANTY 2 years - Ask for warranty sheet for	details						
TECHNICAL SPECIFICATIONS (usin							
Grid Material	Flexible PVC (Ribbed Grid)						
Carpet Fiber*:	100% Solution-dyed, UV stabilized ASOTA™ polypropylene						
Dimensional Stability (ASTM D7570	Non-woven hobnail (berber) pattern) 0-09)* Pass						
Electrostatic Propensity (EN 1815)*							
Electrical Resistivity (IBM / ICL)*	Pass, for R.H. ≥ 40%						
Sound Insulation (ISO 10140-1:201	0)* ≥ 21dB						
Thermal Retention (ISO 11092)*	0.15 m K/W Pass						
COLOR FASTNESS (using Centaur	Carpet)						
To Light (ISO 105 B02)*	5	-					
To Water (ISO 105 B01)*	5						
To Shampoo (ISO 105 B06)* To Rubbing (ISO 105 B02)*	4-5 Dry: 4 Wet: 3-4						
TO RUDDING (ISO TOS BUZ)"	⊅ry. 4 vvet: 3-4						
FLAMMABILITY		-					
Smoke Density (ASTM E662)	Passes						

Passes

ENVIRONMENT

Langhorn Flooring Concepts does not use any substances currently included in the SVHC (Substances of Very High Concern) list under REACH (Registration, Evaluation, Authorization and Restriction of Chemical substances) in any matting products. All PVC grid products are 100% recyclable.

Surface Flammability (FF 1-70/ASTM D2859)

LEED-NC: MR CREDIT 4 IEQ CREDITS 4.1, 4.3, 5

MAINTENANCE

DAILY: Vacuum with an industrial cleaner. Should stones, salt particles or other solid matter become embedded between the surface ribs, remove using a blunt instrument (screwdriver) or similar device. In addition to daily routine above, its important to remove chewing gum deposits and stains as they appear.

WEEKLY: Complete daily cleaning routine, then clean top surface using cylindrical brush machine. Initially work in direction of top ribs then across the ribs to complete cleaning. If a cylindrical brush machine is not available equally good results can be achieved using a high-pressure water extraction process.

For more information on Two-n-One installation or maintenance,

١	10	7	П	IR)	Λ	ı	ΙT	Ъ		R	17	' F) <	. ^	. 1	ES	R	F	D	D	F	≤ 1	F	N	ĺΤ	٧.	ΤI	\/	F	
	ľί	J	U	ıĸ		Α	U.	, ,	П	Ų,	ıĸ	1 /	. Е	L		\sim	۱L	$E \supset$	ĸ		М	ĸ	Е.	.)		$ \rangle$	1	\mathcal{A}	11	V		

LFC_2N1_100821		Langhorn Flooring Concepts