

# Classic beauty that supports your workers throughout the day.

Premium Marbleized mat smooth wear layer is puncture resistant and easy to clean, while the expanded foam sponge reduces stress on legs and joints for added comfort and performance. Its beveled edges reduce trip, slip and fall accidents, and its moisture-resistant engineering make it suitable for most any environment.

- PVC/Nitrile Rubber.
- Provides comfortable cushioned work surface.
- Improves morale and increases productivity.
- Reduces noise and insulates.



01. Grey/White/Black



02. Blue



03. Black/White



## Premium Marbleized Anti-Fatigue









### ANTI-FATIGUE | 1/2 SMOOTH PATTERNED MATTING

#### SUGGESTED USES (Not limited to)

Checkstands, floral departments, offices, light-duty work areas.

Manufacturing Process:
Wear Surface:
Underside:
Gauge:
Weight:
Underside Density:

Fusion Bonded Plastic
Rubber (1/8")
Closed-Cell PVC Foam (3/8")
Closed-Cell PVC Foam (3/8")
- 1.5 lbs./sq. ft.
20 lbs./cu. ft.

Available Colors: Grey (standard), Blue, Tan, Black, Brown Available Sizes  $2' \times 3' \mid 2' \times 60' \mid 3' \times 5' \mid 3' \times 60' \mid 4' \times 60'$ 

#### LIMITED WARRANTY

Full Commercial 1 year Summary of Warranty:

Langhorn Flooring Inc. warrants Marbleized Anti-Fatigue Matting against wear for a period of 1 year in a commercial application. This warranty applies only to material that is properly installed and maintained, while being used as intended and recommended. If the defect is covered by this warranty and is reported to Langhorn Flooring Inc. within the Warranty period, Langhorn Flooring Inc. will supply new material of same or similar grade to repair or replace the defective material.

#### Wear

Defined as complete removal of wear layer, pattern and color due to wear from normal traffic and maintenance. If the wear occurs within 1 year from date of purchase, Langhorn Flooring Inc. will provide replacement materials or repair, of only the effected area.

#### • Manufacturing Defects

Langhorn Flooring Inc. warrants Marbleized Anti-Fatigue Matting materials are free from manufacturing defects and will replace defective floor covering and reasonable installation costs for a period of up to one [1] year from date of purchase. Langhorn Flooring Inc. will not pay labor costs to repair or replace materials that defects were apparent before or at the time of installation.

#### Other Limitations

- This warranty is non-transferable
- Manufacturing defect must be reported within 3 months from date of purchase.
- This Warranty covers only properly installed & maintained floors
- Langhorn Flooring Inc. excluded and will not pay for any consequential or incidental expenses.
- Langhorn Flooring Inc. reserves the right of final judgment and may refuse claims in certain instances.
- \*For a copy of the full warranty please ask for a warranty sheet

#### **TECHNICAL SPECIFICATIONS**

Tensile Strength (ASTM D412): 1200 lbs/sq. in. Graves Tear Strength (ASTM D1004): 150 lbs. Elongation (ASTM D412): 200% Longitudinal Abrasion Resistance: < 1% Loss Taber Abrasion: 1000 cycles, 1000g load, CS-17 Wheel Hardness (ASTM D2240): 80 ±5 (Shore 'A'); 6 months aging (negligible)

Compression: 12% Max Static Coefficient of Friction (ASTM C1028): 0.78 (Dry)

#### **FLAMMABILITY**

Flame Resistance (FMVSS 302)

Pass

#### **MAINTENANCE**

NOTES:

Marbleized Step can be mopped or wiped clean with a damp cloth.

#### IMPORTANT NOTICE

Sample swatches have been cut from an overall design; decoration and shade may vary.

#### YOUR AUTHORIZED SALES REPRESENTATIVE:

TOOK AOTHORIZED SALES KELK	LJLINIAIIVL.
21	
002	
4	A DIVISON OF VAN GELDER INC.
C_MAF_100521	Langhorn Flooring Concepts
7	Langitoiti
	Flooring Concepts