

# Natures Edge

LUXURY VINYL PLANKS | RUSTIQUE COLLECTION 40MIL | 7" X 48"



01. Antique Brown NVR9415\*



02. Dove NVR7283



03. Cape Cod Grey NVR7285



04. Silver Sand NVR6841



05. Anchor Grey NVR6846



06. Wheatfields NVR9825



07. Canyon Dust Cross-Cut NVR5476\*



08. Honduran Rosewood NVR9822



09. African Blackwood NVR9848




10. Sundried Teak NVR7305



11. Windswept Beige NVR9844



12. Oak Barrel NVR9675



13. Whiskey Cross-Cut NVR5478\*

The warmth and appeal of hardwood with the resilience and easy maintenance of vinyl.

Nature's Edge luxury vinyl provides more cushioning, shock absorbency and versatility when needed for sports, recreational, multi-purpose and anti-fatigue flooring. Natures Edge combines a rubber backing that offers excellent support, while our Langhorn 1x coating gives superior stain, scratch, and scuff resistance.

\*Note: Antique Brown NER9415, Canyon Dust Cross-Cut NER5476 and Whiskey Cross-Cut NER5478 are not registered embossed.

A DIVISION OF VAN GELDER INC.  
**Langhorn**  
Flooring Concepts

Your Source for  
Commercial Fitness Flooring  
1+(706) 602-4186 • [www.langhornfci.com](http://www.langhornfci.com)

# Natures Edge



LUXURY VINYL PLANKS | RUSTIQUE COLLECTION 40MIL | 7" X 48"

## SUGGESTED USES

Beauty Salons, Conference Rooms, Corporate Lunchrooms, General Office, Hospitals, Libraries, Pharmacies, Retail/Department Stores, Resorts, Restaurants, Spas and Supermarkets

Manufacturing Standard: Class III Printed Film Vinyl Plank; 1x Coated Registered Embossed Surface\*

Overall Thickness 3.175mm | 0.125"

Wear Layer Thickness 1.0mm | 40mil

Plank Size 7" x 48"

## LIMITED WARRANTY

Full Commercial Warranty 21 years

### Summary of Warranty:

Natures Edge planks must be professionally installed to validate the warranty. Langhorn Flooring Concepts Inc. warrants Natures Edge Style Rustique first quality planks against wear for a period of 21 years in a commercial application. This warranty applies only to material that is properly installed and maintained, while being used as intended and recommended. If the defect is covered by this warranty and is reported to Langhorn Flooring Concepts Inc. within the Warranty period, Langhorn Flooring Concepts Inc. will supply new material of same or similar grade to repair or replace the defective material.

### Wear

Defined as complete removal of wear layer, pattern and color due to wear from normal traffic and maintenance. If the wear occurs within 21 years from date of purchase, Langhorn Flooring Concepts Inc. will provide replacement materials or repair, of only the effected area.

### Manufacturing Defects

Langhorn Flooring Concepts Inc. warrants Style Rustique first quality plank materials are free from manufacturing defects and will replace defective floor covering and reasonable installation costs for a period of up to one [1] year from date of purchase. Langhorn Flooring Concepts Inc. will not pay labor costs to repair or replace materials that defects were apparent before or at the time of installation.

### Other Limitations

- This warranty is non-transferable
- Manufacturing defect must be reported within 3 months from date of purchase.
- This Warranty covers only properly installed & maintained floors
- Langhorn Flooring Concepts Inc. excluded and will not pay for any consequential or incidental expenses.
- Langhorn Flooring Concepts Inc. reserves the right of final judgment and may refuse claims in certain instances.

\*For a copy of the full warranty please ask for a warranty sheet

## PACKAGING & DIMENSIONS

Plank 7" x 48": 15 planks/carton  
 Sq. Ft. per carton: 35 sq. ft  
 Weight: 34.81 lbs./carton

## TECHNICAL SPECIFICATIONS (ASTM 1700-99)

Stability (EN 986)	Pass
Abrasion Resistance (EN 660)	Excellent (<0.15g/1000 cycles)
Static Load (ASTM F970 - Modified)	2000 psi
Sound Insulation (DIN 52210)	4dB
Slip Resistance (ASTM D 2047)	Pass (0.61 - Exceeds ADA Standards)
Stain & Chemical Resistance (ASTM 925)	Pass
Light Resistance (F 1515)	Pass
Indentation Resistance (F 1914)	Pass (<8%)

## FLAMMABILITY RATING

Radiant Panel Test (ASTM E648)	Class 1
Smoke Density (ASTM E662)	Pass (<450 sdi)
Heat Stability (ASTM 1514)	Pass


HUD/FHA Requirements

Exceeds

## IMPORTANT NOTICE

Sample swatches have been cut from an overall design, decoration & shade may vary. The random nature of wood and other natural materials from which our patterns are designed means that significant color and design variation is normal and enhances the look of the planks.

## PRODUCT CONSTRUCTION



## MAINTENANCE

We recommend using a non-rising cleaner that leaves no film and suggest that you vacuum, sweep or dust mop twice per week. High-traffic areas might require more frequent cleaning.

Wipe up food and other spills immediately using recommended cleaner and a soft cloth. You should NEVER USE ABRASIVE CLEANERS, POWDERS, OIL CLEANERS, WAXES OR DISH DETERGENT. These will scratch the surface or leave a film.

When using a vacuum, if possible turn off the beater and use a hose or wand with an upholstery attachment. Vacuum wheel may also be a source for indenting and scuffing, check the wheels for embedded grit.

To remove scuff marks you can use a soft cloth to rub it out. If they difficult to remove try using a product named "Oops Painter Wipes". Rinse the area well afterwards with clean warm water and allow to dry. Please note that these procedures may help remove stains from vinyl floors, but cannot guarantee complete removal. Burns, holes or "permanent" stains may require a replacement "patch of that section of the floor.

To remove damaged planks you can use a hair dryer, which heats up the adhesive allowing the plank to be picked up. When the plank is up, use a wide blade putty knife and pull it out, then put the new plank down once the surface has been prepared. You should NEVER USE A HEAT GUN as this emits too much heat and will damage the planks.

## YOUR AUTHORIZED SALES REPRESENTATIVE:

LFC\_NER40\_7X48\_100821